




	• STANDARD 20'		• UPGRADED 20'	
Inside length	19'4"	5.89 m	19'4"	5.89 m
Inside width	7'8"	2.33 m	7'7"	2.31 m
Inside height	7'10"	2.38 m	7'10"	2.38 m
Door width	7'8"	2.33 m	7'6"	2.28 m
Door height	7'6"	2.28 m	7'6"	2.28 m
Capacity	1,172 ft ³	33.18 m ³	1,150 ft ³	32.56 m ³
Tare weight	4,916 lb	2,229 Kg	5,060 lb	2,229 Kg
Max. cargo	47,999 lb	21,727 Kg	61,996lb	28,120 Kg
	• STANDARD 40'		• HIGH CUBE 40'	
Inside length	39'5"	12.01 m	39'5"	12.01 m
Inside width	7'8"	2.33 m	7'8"	2.33 m
Inside height	7'10"	2.38 m	8'10"	2.69 m
Door width	7'8"	2.33 m	7'8"	2.33 m
Door height	7'6"	2.28 m	8'5"	2.56 m
Capacity	2,390 ft ³	67.67 m ³	2,694 ft ³	76.28 m ³
Tare weight	8,160 lb	3,701 Kg	8,750 lb	3,968 Kg




	• OPEN TOP 20'		• OPEN TOP 40'	
Inside length	19'4"	5.89 m	39'5"	12.01 m
Inside width	7'7"	2.31 m	7'8"	2.33 m
Inside height	7'8"	2.33 m	7'8"	2.33 m
Door width	7'6"	2.28 m	7'8"	2.23 m
Door height	7'2"	2.18 m	7'5"	2.26 m
Capacity	1,136 ft ³	32.16 m ³	2,350 ft ³	66.54 m ³
Tare weight	5,280 lb	2,394 Kg	8,490 lb	3,850 Kg



				
	• REEFER 20'		• REEFER 40'	
Inside length	17'8"	5.38 m	37'8"	11.48 m
Inside width	7'5"	2.26 m	7'5"	2.26 m
Inside height	7'5"	2.26 m	7'2"	2.18 m
Door width	7'5"	2.26 m	7'5"	2.26 m
Door height	7'3"	2.20 m	7'0"	2.13 m
Capacity	1,000 ft ³	28.31 m ³	2,040 ft ³	57.76 m ³
Tare weight	7,040 lb	3,193 Kg	10,780 lb	4,889 Kg
Max. cargo	45,760 lb	20,756 Kg	56,276 lb	25,526 Kg
	• REEFER 40' HIGH CUBE			
Inside length	37'11"	11.55 m		
Inside width	7'6"	2.28 m		
Inside height	8'2"	2.48 m		
Door width	7'6"	2.28 m		
Door height	8'0"	2.43 m		
Capacity	2,344 ft ³	66.37 m ³		
Tare weight	9,900 lb	4,490 Kg		
Max. cargo	57,561 lb	26,109 Kg		



				
	• FLAT RACK 20'		• FLAT RACK 40'	
Inside length	18'5"	5.61 m	39'7"	12.06 m
Inside width	7'3"	2.20 m	6'10"	2.08 m
Inside height	7'4"	2.23 m	6'5"	1.95 m
Tare weight	5,578 lb	2,530 Kg	12,081 lb	5,479 Kg
Max. cargo	47,333 lb	21,469 Kg	85,800 lb	38,918 Kg



	• FLAT RACK COLLAPSIBLE 20'		• FLAT RACK COLLAPSIBLE 40'	
Inside length	18'6"	5.63 m	39'7"	12.06 m
Inside width	7'3"	2.20 m	6'10"	2.08 m
Inside height	7'4"	2.23 m	6'5"	1.95 m
Tare weight	6,061 lb	2,749 Kg	12,787 lb	5,800 Kg
Max. cargo	61,117 lb	27,722 Kg	85,800 lb	38,918 Kg



	• PLATFORM 20'		• PLATFORM 40'	
Inside length	19'11"	6.07 m	40'0"	12.19 m
Inside width	8'0"	2.43 m	8'0"	2.43 m
Inside height	7'4"	2.23 m	6'5"	1.95 m
Tare weight	6,061 lb	2,749 Kg	12,783 lb	5,798 Kg



	• CHASSIS 23'6"		• CHASSIS 40' GOOSENECK	
Lenght	overall extended 27'6"	lung. max.esteso 8.25 m	overall extended 40'	lung. max.esteso 12.00 m
Tare weight	6,500 lb	2,954 Kg	6,500 lb	2,954 Kg
Max. cargo	39,500 lb	17,955 Kg	44,500 lb	20,227 Kg
	• CHASSIS 33' TRI-AXLE			
Lenght	overall extended 41'3"	lung. max.esteso 12.37 m		
Tare weight	10,900 lb	4,954 Kg		
Max.cargo	44,500 lb	20,227 Kg		
Lenght	overall unextended 33'3"	lung. max.esteso 9.97 m		
Tare weight	10,900 lb	4,954 Kg		